


Instalok™ Couplings - cont.

- Couplings are made of galvanized steel
- Standard O-ring is black nitrile
- Viton O-rings are also available
- Also offering replacement O-rings, nuts, bolts and clamps

OD	NPS	O-RING	LENGTH (in.)	PART NO.
3"	-	Black	4	CP30042B-16Z
3"	-	White	4	CP30042W-16Z
3"	-	Black	6	CP30062B-16Z
3"	-	White	6	CP30062W-16Z
3"	-	Black	8	CP30082B-16Z
3"	-	White	8	CP30082W-16Z
3-1/2"	3"	Black	4	CP35042B-16Z
3-1/2"	3"	White	4	CP35042W-16Z
3-1/2"	3"	Black	6	CP35062B-16Z
3-1/2"	3"	White	6	CP35062W-16Z
3-1/2"	3"	Black	8	CP35082B-16Z
3-1/2"	3"	White	8	CP35082W-16Z
4"	3-1/2"	Black	4	CP40042B-16Z
4"	3-1/2"	White	4	CP40042W-16Z
4"	3-1/2"	Black	6	CP40062B-16Z
4"	3-1/2"	White	6	CP40062W-16Z
4"	3-1/2"	Black	8	CP40082B-16Z
4"	3-1/2"	White	8	CP40082W-16Z
4-1/2"	4"	Black	6	CP45062B-16Z
4-1/2"	4"	White	6	CP45062W-16Z
4-1/2"	4"	Black	8	CP45082B-16Z
4-1/2"	4"	White	8	CP45082W-16Z

When Ordering,
Please Specify
Type of Material:

- Zinc-Coated
(Galvanized)



Instalok™ Coupling




Specifications

- 1-1/2" OD to 4-1/2" OD
- 20% Lower cost than traditional couplings
- 30% Quicker installation
- Couplings have a unique clamping design that offers unparalleled strength and grip
- Made with Grade 5 stress relieved bolts to ensure a trouble-free installation

KEY

OD = Outside Diameter
NPS = Nominal Pipe Size
All reference dimensions are nominal.



MAX FLOW
TUBING & FITTINGS 19